



Passenger car engine oils - Fully Synthetic

Miles 5W-20

Fully synthetic oil for gasoline and diesel engines, with or without turbo

Description

Miles 5W-20 is a fully synthetic motor oil for gasoline and diesel engines in passenger cars and light duty commercial vehicles. This oil can be applied for cars equipped with catalytic converters, turbo charged engines and for direct fuel injection systems.

Miles 5W-20 provides an extremely quick and stable lubricant film at the cold start and offers high thermal stability under heavy duty operating conditions.

Miles Super Lite 5W-20 not only offers extremely good wear protection, but also protects against rust and corrosion, while special additives keep all parts free from dirt, sludge and deposits.

Miles 5W-20 offers fuel saving properties and can be mixed with both synthetic and mineral motor oils.

Performance level

- API SN/CF

Physical properties

Colour	amber	
Density at 20°C	0.846 kg/l	ASTM D 4052
Viscosity, kinematic at 40°C	47.8 cSt	ASTM D 445
Viscosity, kinematic at 100°C	8.7 cSt	ASTM D 445
Viscosity Index	163	ASTM D 2270
Viscosity, dynamic (CCS)	3880 cP	ASTM D 5293
Base number	8.5 mg	ASTM D 2896
Sulphated ash	0.85 wt%	ASTM D 874
Flash point	209 °C	ASTM D 93
Pour point	-39 °C	ASTM D 97